

SYM車種別キャブレターセッティングデータ

2008.6.4現在

Name	Model	Venturi dia.(mm)	Float level(mm)	Main jet	Slow jet	Idle speed	Pilot screw opening	Spark plug
RV250	LM25W-7	28.8	18.5	112	40	1800±100rpm	2 ±1/2	CR7E
FIGHTER150	HV15V1-7	23	18	105	35	1800±100rpm	2 1/4	CR8E
RV125JP	LA12W2-7	24	18.5	108	35	1800±100rpm	2 1/4	CR8E
RV180JP	LA18W-7	25	18.5	108	35	1800±100rpm	2 1/2	CR8E
GT125	HM12VA-7	22.1	17.5	92	35	1700±100rpm	2 1/2	CR7E
Attila125	T3DB-J	23	18.5	102	32	1700±100rpm	2 1/2~3	A7RC
X'PRO100	HK10V-7	20	20.5	95	35	1700±100rpm	2 ±1/2	C6HSA
Umi100	HU10W-7	20	16	95	38	1700±100rpm	2 5/8±3/4	C6HSA
SYMPLY/ FIDDLE X	AV05W1-6 AW05W1-6		3.5	85	35	2100±100rpm	1 1/2±3/4	A7RC
Umi50	HU05U-7	16.6	17.75	88	35	2000±100rpm	2 ±1/2	C6HSA
X'PRO風50	HP05U-7	16.6	17.75	92	35	2000±100rpm	2 ±1/2	C6HSA
DD50	FT05V-7	14	8.6	88	38	2000±100rpm	1 1/4(±3/4)	BR8HSA
Fiddle50	FA05A-7	14	8.6	88	38	2000±100rpm	1 1/4(±3/4)	BR8HSA